# CS 725/825 & IT 725 Lecture 13 Network Management Transport Layer

# Network Management


## Network Management

- Networks are complicated...
- Targets of management:
  - configuration
  - faults
  - performance
  - security
  - accounting

## Network Management

- Two aspects of management
  - information collection and dissemination
  - decision making
- Components:
  - managed node
  - management station
  - management protocol
  - management information base (MIB)

## Network Management



### Management Protocols

- Simple Network Management Protocol (SNMP)
  - another "simple" protocol...
  - polling and trapping
  - data representation (ASN.1)
  - object identifiers (OIDs)
- OID Example
  - iso(1) identified-organization(3) dod(6) internet(1) mgmt(2) mib-2(1) ip(4) ipInReceives(3)
  - -1.3.6.1.2.1.4.3

### NETCONF

#### Network Configuration Protocol (NETCONF)

- "provides mechanism to install, manipulate, and delete the configuration of network devices." (RFC 6241)
- XML-based, realized as remote procedure calls (RPC)
- underlying transport must provide authentication and authorization
- a NETCONF implementation must support ssh transport

#### **YANG**

- data modeling language
- describes data structures, data integrity constants, and data operations
- ... Yet Another Next Generation

# Transport Layer

## Transport Layer

- Big leap in the level of abstraction:
  - Application Layer: reliable, bidirectional, stream-oriented service
  - Network Layer: unreliable datagram service
- End-to-End Principle
  - as simple as possible network
  - all "smarts" at the end nodes


### Functions of Transport Layer


- Addressing
  - port numbers (?)
- Error control
  - packet loss detection and retransmissions
- Flow and congestion control
  - controlling the transmission rate
- Session management

### Principles of Reliable Transport


- ▶ Goal: deliver despite unreliability of the network layer or detect that delivery is not possible
- Automatic Repeat reQuest (ARQ):
  - acknowledgment
  - timeout
  - retransmission
  - give up after *k* retransmissions
  - sequence numbers on data packets
  - cumulative acknowledgment numbers

#### COMPONENTS OF ARB





#### ACL #'s - MOTIVATION



### Cumulative ACK numbers

- Method 1 (obvious but not used):
  - ACK carries the sequence number of the packet it acknowledges
- Method 2 (Cumulative ACK, used by TCP)
  - ACK carries the lowest sequence number of the packets that were not yet received (sequence number of the next expected packet)

